



## Color Décor Primer

### DESCRIPTION

Economical interior/exterior primer spray at any angle, comfort spray tip.

### ENVIRONMENTAL STATEMENT

Contains no CFC's which deplete the ozone layer



#### Color Décor Primer

**TYPE:** VT Alkyd, decorative, fast drying

#### VOC/MIR

VOC & MIR COMPLIANT

Maximum 60% VOC & 1.2pw MIR for flat enamels and primers.

#### GLOSS AT 60°

Primers: 5-20

**PERCENT SOLIDS BY WEIGHT** 17.12%

#### COLOR

CDS-8 Gray Primer

#### Product Features

•Fast Drying

#### FLASH POINT

< 20° F.

### RECOMMENDED USE:

For interior or exterior wood, metal, furniture, wicker crafts and other paintable surfaces. Do not use on Styrofoam, ceramic tiles or marble.

**DRY TIME:** Dry to touch in 20 minutes. Tack free in 3-4 hours. Recoat within one hour. High humidity or low temperature may increase dry time.

**DISPOSAL:** Dispose of aerosol container and unused contents in accordance with local, state and federal regulations. Do not burn, incinerate, puncture or place aerosol container in home garbage compactor.

**CLEAN UP:** Never stick sharp objects into the opening at the top of the can. For wet film, use mineral spirits. For dry film, use paint stripper, toluol or acetone.

**DISPOSAL:** To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only) or go to [www.Earth911.org](http://www.Earth911.org).

**STORAGE:** Do not store at temperatures above 120°F (50°C). Protect unused product from freezing.

### APPLICATION METHODS

- Before spraying, shake can for two minutes after ball within begins to rattle
- Shake can occasionally during use
- Hold can 10" to 16" (25 to 40 cm) away from the surface
- For a smooth finish, spray in a sweeping motion
- To avoid runs and drips, apply several thin coats rather than one heavy coat

### Surface Prep:

- Remove all grease, oil, dirt, wax and rust scale from surface.
- On new, bare and rusty surfaces Color Décor or XOP Primer is recommended
- New galvanized surfaces must weather 6 months before priming.
- Use with adequate ventilation.

### WARNINGS

Contains propane, acetone and aromatic solvents. Extremely flammable. Storage and handling: Level-3 Aerosols.