

Premium Décor Appliance Epoxy



DESCRIPTION

Superior interior/exterior appliance epoxy spray at any angle, comfort spray tip. Formulated for household appliances and tools. Produces a uniform, hard finish that resists dirt and stains.

ENVIRONMENTAL STATEMENT

Contains no CFC's which deplete the ozone layer



Premium Décor Epoxy

TYPE: Epoxy alkyd

VOC/MIR

VOC & MIR COMPLIANT

Maximum 65% VOC & 1.4 pw MIR for gloss and satin enamels.

GLOSS AT 60°

Gloss Enamels: 80-100

PERCENT SOLIDS BY WEIGHT: 17.69%

PDS-1544

COLORS

PDS-1538 White

PDS-1539 Black

PDS-1544 Almond

Product Features

•Fast Drying

•Lasts Longer

•Resists Chipping

FLASH POINT

< 20° F.

RECOMMENDED USE:

Appliances, interior sealed wood, metal, plaster, drywall and tools. Do not use on Styrofoam, ceramic tiles or marble. Do not use on ovens or inside dryers.

DRY TIME: Dry to touch in 10-25 minutes. Tack free in 3-5 hours. Recoat within one hour. High humidity or low temperature may increase dry time.

DISPOSAL: Dispose of aerosol container and unused contents in accordance with local, state and federal regulations. Do not burn, incinerate, puncture or place aerosol container in home garbage compactor.

CLEAN UP: Never stick sharp objects into the opening at the top of the can. For wet film, use mineral spirits. For dry film, use paint stripper, toluol or acetone.

DISPOSAL: To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only) or go to www.Earth911.org.

STORAGE: Do not store at temperatures above 120°F (50°C). Protect unused product from freezing.

APPLICATION METHODS:

- Before spraying, shake can for two minutes after ball within begins to rattle Shake can occasionally during use
- Hold can 10" to 16" (25 to 40 cm) away from the surface
- For a smooth finish, spray in a sweeping motion
- To avoid runs and drips, apply several thin coats rather than one heavy coat

Surface Prep:

- Remove all grease, oil, dirt, wax and rust scale from surface.
- On new, bare and rusty surfaces Premium Décor or XOP Primer is recommended.
- New galvanized surfaces must weather 6 months before priming.
- Use with adequate ventilation.

WARNINGS

Contains propane, acetone and aromatic solvents. Extremely flammable. Storage and handling: Level-3 Aerosols.