



## Premium Décor Decorative Finish Flat Enamel

### DESCRIPTION

Superior interior/exterior decorative enamel spray at any angle, comfort spray tip.

### ENVIRONMENTAL STATEMENT

Contains no CFC's which deplete the ozone layer



### PDS Premium Décor Flat

**TYPE:** Modified Acrylic Alkyd, decorative, fast drying

#### VOC/MIR

VOC & MIR COMPLIANT

Maximum 60% VOC & 1.2 pw MIR for flat enamels.

#### GLOSS AT 60°

Flat Enamels: 0-5

**PERCENT SOLIDS BY WEIGHT** 20.45%

### COLORS

PDS-5 Flat White

PDS-6 Flat Black

### FLASH POINT

< 20° F.

### Product Features

- Fast Drying
- Popular decorative colors
- Spray at any angle comfort tip
- Lasts Longer

### RECOMMENDED USE:

For interior or exterior wood, metal, furniture, wicker crafts and other paintable surfaces. Do not use on Styrofoam, ceramic tiles or marble.

**DRY TIME:** Dry to touch in 0-10 minutes. Tack free 20-45 minutes. Recoat within one hour. High humidity or low temperature may increase dry time.

**DISPOSAL:** Dispose of aerosol container and unused contents in accordance with local, state and federal regulations. Do not burn, incinerate, puncture or place aerosol container in home garbage compactor.

**CLEAN UP:** Never stick sharp objects into the opening at the top of the can. For wet film, use mineral spirits. For dry film, use paint stripper, toluol or acetone.

**DISPOSAL:** To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only) or go to [www.Earth911.org](http://www.Earth911.org).

**STORAGE:** Do not store at temperatures above 120°F (50°C). Protect unused product from freezing.

### APPLICATION METHODS

- Before spraying, shake can for 2 minutes after ball within begins to rattle and occasionally during use.
- Hold can 10" to 16" (25 to 40 cm) away from the surface and apply several thin coats a few minutes apart rather than one heavy coat, slightly overlapping each stroke.
- Keep can in motion while spraying.
- Recoat within one hour.

### Surface Prep:

- Remove all grease, oil, dirt, wax and rust scale from surface.
- On new, bare and rusty surfaces Premium Décor or XOP Primer is recommended.
- New galvanized surfaces must weather 6 months before priming.
- Use with adequate ventilation.

### WARNINGS

Contains propane, acetone and aromatic solvents. Extremely flammable. Storage and handling: Level-3 Aerosols.