



Premium Décor Fluorescent

DESCRIPTION

Superior interior/exterior flat, fluorescent, fast drying enamel spray at any angle, comfort spray tip.

ENVIRONMENTAL STATEMENT

Contains no CFC's which deplete the ozone layer



Premium Décor Fluorescent

TYPE: Flat, fluorescent, fast drying

VOC/MIR

VOC & MIR COMPLIANT

Maximum 65% VOC & 1.75 pw MIR

GLOSS AT 60°

Gloss Enamels: 0-10

PERCENT SOLIDS BY WEIGHT: 35.21%

COLORS

PDFL-1 Blazing Orange

PDFL-2 Hot Red

PDFL-3 Bright Yellow

PDFL-4 Neon Blue

PDFL-5 Neon Blue

PDFL-6 Red Orange

PDFL-7 Electric Pink

Product Features

- Fast Drying
- Bold, Bright Colors
- Lasts Longer

FLASH POINT

< 20° F.

RECOMMENDED USE:

For marking and crafts. Also can be used on wood, metal, furniture, handcrafts and other paintable surfaces. Do not use on Styrofoam, ceramic tiles or marble.

DRY TIME: Dry to touch in 5-20 minutes. Tack free in 30-45 minutes. Recoat within one hour. High humidity or low temperature may increase dry time.

DISPOSAL: Dispose of aerosol container and unused contents in accordance with local, state and federal regulations. Do not burn, incinerate, puncture or place aerosol container in home garbage compactor.

CLEAN UP: Never stick sharp objects into the opening at the top of the can. For wet film, use mineral spirits. For dry film, use paint stripper, toluol or acetone.

DISPOSAL: To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only) or go to www.Earth911.org.

STORAGE: Do not store at temperatures above 120°F (50°C). Protect unused product from freezing.

APPLICATION METHODS

- Before spraying, shake can for two minutes after ball within begins to rattle
- Shake can occasionally during use
- Hold can 10" to 16" (25 to 40 cm) away from the surface
- For a smooth finish, spray in a sweeping motion
- To avoid runs and drips, apply several thin coats rather than one heavy coat

Surface Prep:

- Remove all grease, oil, dirt, wax and rust scale from surface.
- On new, bare and rusty surfaces Premium Décor or XOP Primer is recommended.
- New galvanized surfaces must weather 6 months before priming.
- Use with adequate ventilation.

WARNINGS

Contains propane, acetone, aromatic solvents and petroleum distillates. Extremely flammable. Storage and handling: Level-3 Aerosols.