

Premium Décor Decorative Finish Gloss Enamel



DESCRIPTION

Superior interior/exterior decorative enamel spray at any angle, comfort spray tip.

ENVIRONMENTAL STATEMENT

Contains no CFC's which deplete the ozone layer

PDS Premium Décor Gloss

TYPE: Modified Acrylic Alkyd, decorative, fast drying

VOC/MIR

VOC & MIR COMPLIANT

Maximum 65% VOC & 1.4 pw MIR for gloss

67% VOC & 1.5 pw MIR for Clear

GLOSS AT 60°

Gloss Enamels: 80-100

PERCENT SOLIDS BY WEIGHT: PDS-1 19.65%



Product Features

- Fast Drying
- Popular decorative colors
- Lasts Longer

FLASH POINT

< 20° F.

COLORS

- PDS-1 Gloss White
- PDS-2 Gloss Black
- PDS-7 Clear Acrylic Gloss
- PDS-11 Navajo White
- PDS-12 Ivory
- PDS-15 Heirloom White
- PDS-16 Almond
- PDS-20 Awareness Pink
- PDS-24 Banner Orange
- PDS-30 Royal Blue
- PDS-31 Harbor Blue
- PDS-40 Sunflower Yellow
- PDS-41 Daffodil
- PDS-50 Hunter Green
- PDS-52 Meadow Green
- PDS-60 Leather Brown
- PDS-70 Slate Gray
- PDS-71 Pewter Gray
- PDS-95 Shutter Red
- PDS-96 Fiesta Red
- PDS-97 Hot Red
- PDS-100 Caribbean Water
- PDS-101 Pumpkin Orange
- PDS-102 Apple Green
- PDS-103 Plum Purple

RECOMMENDED USE:

For interior or exterior wood, metal, furniture, wicker crafts and other paintable surfaces. Do not use on Styrofoam, ceramic tiles or marble.

DRY TIME: Dry to touch in 0-10 minutes. Tack free 20-45 minutes.

Recoat within one hour. High humidity or low temperature may increase dry time.

DISPOSAL: Dispose of aerosol container and unused contents in accordance with local, state and federal regulations. Do not burn, incinerate, puncture or place aerosol container in home garbage compactor.

CLEAN UP: Never stick sharp objects into the opening at the top of the can. For wet film, use mineral spirits. For dry film, use paint stripper, toluol or acetone.

DISPOSAL: To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only) or go to www.Earth911.org.

STORAGE: Do not store at temperatures above 120°F (50°C). Protect unused product from freezing.

APPLICATION METHODS

- Before spraying, shake can for 2 minutes after ball within begins to rattle and occasionally during use.
- Hold can 10" to 16" (25 to 40 cm) away from the surface and apply several thin coats a few minutes apart rather than one heavy coat, slightly overlapping each stroke. Keep can in motion while spraying.
- Recoat within one hour.

Surface Prep:

- Remove all grease, oil, dirt, wax and rust scale from surface.
- On new, bare and rusty surfaces Premium Décor or XOP Primer is recommended.
- New galvanized surfaces must weather 6 months before priming.
- Use with adequate ventilation.

WARNINGS

Contains propane, acetone, aromatic solvents and petroleum distillates. Extremely flammable.

Storage and handling: Level-3 Aerosols.