



Premium Décor Lacquer

DESCRIPTION

Superior interior/exterior decorative lacquer enamel spray at any angle, comfort spray tip. Great for use on wood, metal and furniture. Easy to sand.

ENVIRONMENTAL STATEMENT

Contains no CFC's which deplete the ozone layer



Premium Décor Lacquer

TYPE: Genuine lacquer

VOC/MIR

VOC & MIR COMPLIANT

Maximum 65% VOC & 1.4 pw MIR for PD1353 & PD 1354 (Black & White)

Maximum 67% VOC & 1.5 pw MIR for PD1355 Clear

GLOSS AT 60°

Gloss Enamels: 80-100

PERCENT SOLIDS BY WEIGHT : 15.45%

PDS-1353

COLORS

PDS-1353 Black

PDS-1354 White

PDS-1355 Clear

Product Features

- Fast Drying
- High Gloss Sheen
- Lasts Longer

FLASH POINT

< 20° F.

RECOMMENDED USE:

For wood, metal, furniture, tools, handcrafts and other paintable surfaces. Do not use on Styrofoam, ceramic tiles or marble.

DRY TIME: Dry to touch in 5-20 minutes. Tack free in 15-45 minutes. Recoat anytime. High humidity or low temperature may increase dry time.

DISPOSAL: Dispose of aerosol container and unused contents in accordance with local, state and federal regulations. Do not burn, incinerate, puncture or place aerosol container in home garbage compactor.

CLEAN UP: Never stick sharp objects into the opening at the top of the can. For wet film, use mineral spirits. For dry film, use paint stripper, toluol or acetone.

DISPOSAL: To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only) or go to www.Earth911.org.

STORAGE: Do not store at temperatures above 120°F (50°C). Protect unused product from freezing.

APPLICATION METHODS

- Before spraying, shake can for two minutes after ball within begins to rattle
- Shake can occasionally during use
- Hold can 10" to 16" (25 to 40 cm) away from the surface
- For a smooth finish, spray in a sweeping motion
- To avoid runs and drips, apply several thin coats rather than one heavy coat

Surface Prep:

- Remove all grease, oil, dirt, wax and rust scale from surface.
- On new, bare and rusty surfaces Premium Décor or XOP Primer is recommended.
- New galvanized surfaces must weather 6 months before priming.
- Use with adequate ventilation.

WARNINGS

Contains propane, acetone and aromatic solvents & petroleum distillates. Extremely flammable. Storage and handling: Level-3 Aerosols.