



Premium Décor Decorative Finish Satin Enamel

DESCRIPTION

Superior interior/exterior decorative enamel spray at any angle, comfort spray tip.

ENVIRONMENTAL STATEMENT

Contains no CFC's which deplete the ozone layer



PDS Premium Décor Satin

TYPE: Modified Acrylic Alkyd, decorative, fast drying

VOC/MIR

VOC & MIR COMPLIANT

Maximum 65% VOC & 1.4 pw MIR for satin enamels.

GLOSS AT 60°

Satin Enamels: 80-90

PERCENT SOLIDS BY WEIGHT 19.65%

COLORS

PDS-3 Satin White

PDS-4 Satin Black

PDS-8 Clear Acrylic Satin

PDS-116 Almond

PDS-150 Hunter Green

PDS-151 Resin Tan

PDS-152 Burgundy

PDS-153 Army Green

PDS-154 Khaki

Product Features

- Fast Drying
- Popular decorative colors
- Lasts Longer

FLASH POINT

< 20° F.

RECOMMENDED USE:

For interior or exterior wood, metal, furniture, wicker crafts and other paintable surfaces. Do not use on Styrofoam, ceramic tiles or marble.

DRY TIME: Dry to touch in 0-10 minutes. Tack free 20-45 minutes. Recoat within one hour. High humidity or low temperature may increase dry time.

DISPOSAL: Dispose of aerosol container and unused contents in accordance with local, state and federal regulations. Do not burn, incinerate, puncture or place aerosol container in home garbage compactor.

CLEAN UP: Never stick sharp objects into the opening at the top of the can. For wet film, use mineral spirits. For dry film, use paint stripper, toluol or acetone.

DISPOSAL: To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only) or go to www.Earth911.org.

STORAGE: Do not store at temperatures above 120°F (50°C). Protect unused product from freezing.

APPLICATION METHODS

- Before spraying, shake can for 2 minutes after ball within begins to rattle and occasionally during use.
- Hold can 10" to 16" (25 to 40 cm) away from the surface and apply several thin coats a few minutes apart rather than one heavy coat, slightly overlapping each stroke.
- Keep can in motion while spraying.
- Recoat within one hour.

Surface Prep:

- Remove all grease, oil, dirt, wax and rust scale from surface.
- On new, bare and rusty surfaces Premium Décor or XOP Primer is recommended.
- New galvanized surfaces must weather 6 months before priming.
- Use with adequate ventilation.

WARNINGS

Contains propane, acetone, aromatic solvents and petroleum distillates. Extremely flammable. Storage and handling:

Level 2 Aerosols