



Tru-Seal Multi-Surface Waterproofing Sealer

DESCRIPTION:

Clear sealer formulated to protect against moisture damage on small surfaces, outdoor fabrics such as cloth, and leather. Can also be used on brick, patios, hardboard, wood, masonry, concrete and other porous surfaces.

CS-1 FORMULA ANALYSIS

Sheen/Type Finish

Clear

VOC/MIR

VOC & MIR COMPLIANT

Maximum 60% VOC & 1.5pw MIR for clear

GLOSS AT 60°

Clear

Percent Solids by Weight

8.38%

Product Features

- Dries Clear
- Protects and Seals

COLORS

CS-1 Clear

FLASH POINT

< 20° F.

RECOMMENDED USE: For use on small surfaces, outdoor fabrics such as canvas, cloth, carpet and leather. Also protects wood and masonry. Not for fine interior cloth furniture.

DRY TIME: Depends on application and weather conditions.

CLEAN UP: Clean valve by inverting can and pressing valve till gas comes out. Never stick sharp objects into the opening at the top of the can. For wet and dry film, use mineral spirits or paint thinner

DISPOSAL: Dispose of aerosol container and unused contents in accordance with local, state and federal regulations. Do not burn, incinerate or place aerosol container in home garbage compactor.

ENVIRONMENTAL STATEMENT: Contains no CFC's.

APPLICATION METHODS:

Before spraying, shake can for 2 minutes after ball within begins to rattle. Shake can occasionally during use. Hold can 8" to 16" (20 to 40 cm) away from the surface and apply thin coats. Applying too much material will result in non-drying film which can be removed with mineral spirits or paint thinner.

SURFACE PREP:

Remove all grease, oil, dirt and wax from surface. Surface must be porous, thoroughly dry and free from all other coatings. If a small amount of water can be absorbed, the surface is suitable for application.

SURFACE RESTRICTION:

Use on porous surfaces, thoroughly dry and free from other coatings.

WARNINGS

Contains propane, acetone, aromatic solvents and petroleum distillates. Extremely flammable. Storage and handling: Level-3 Aerosols.