



Restorer & Spray Buff

DESCRIPTION

High Speed Restorer & Spray Buff restores finish to a high gloss without build-up.

M-30 FORMULA

Percent solids by weight: 5 to 8 %

Viscosity: Water thin

Weight per US Gallon: 8.38 +/- 0.1 lb

Product Features

- Buffable at high & low speeds
- Removes black heel marks, surface scratches, tar and ingrained dirt
- UL registered

RECOMMENDED USE: All types of resilient flooring such as vinyl, vinyl composite, linoleum, asphalt and rubber tile. Ideal for use on sealed surfaces such as terrazzo and concrete. Use on top of a good acrylic seal or finish for high and low speed burnishing.

HELPFUL HINTS: Maintain surface daily by sweeping and damp mopping using Neutral Cleaner or All Purpose Cleaner. Sweep floors to remove loose dirt and debris. Clean floors with Neutral Cleaner or All Purpose Cleaner, 1 to 8 oz. per gallon water depending on cleanliness of floors. Remove liquid residue. Rinse with water and let dry.

COVERAGE: One gallon (3.78L) covers 5,000 to 10,000 square feet (450 to 900 square meters).

CLEAN UP: N/A

DISPOSAL: Use up or give away excess product . Contains surfactants. Do not reuse container. Empty container may be recycled or placed in trash.

HANDLING & STORAGE: Avoid extreme temperatures. Store in a cool, dry area. Close container after each use. If frozen, thaw and mix before use.

APPLICATION METHODS: Apply full strength with spray bottle just before buffing or burnishing machine. When applied by mop, product can be diluted 1:1 with water then let dry. For buffing and burnishing high speed (1000 rpm) works best but lower speeds will work.

- Avoid contact with eyes and skin. dry.
- Use of rubber gloves are recommended to avoid irritation