



## Floor Finish

### DESCRIPTION

High Speed Restorer & Spray Buff is a high gloss, self sealing finish without buffing or burnishing.

#### M-32 FORMULA

Percent solids by weight: 19.5 to 21 %

Viscosity: Water thin

Weight per US Gallon: 8.54 +/- 0.1 lbs

#### Product Features

- Ultra durable, scrubbable finish, resistant to scuffing and black heel marks
- Excellent slip resistance for use on resilient and non-resilient floors
- UL registered

**RECOMMENDED USE:** Interlocked acrylic polymer for use on all types of resilient flooring including vinyl, vinyl composite, linoleum, asphalt or rubber tile, as well as sealed surfaces such as terrazzo, concrete, wood and cork.

**HELPFUL HINTS:** Avoid flooding against baseboards or under furniture. Test in inconspicuous area to check for appearance and compatibility with surface. A bittering agent has been added to this product to help reduce accidental swallowing. . If appearance of floor is good, wash with Neutral Cleaner or All Purpose Cleaner. Strip questionable finishes with Floor Stripper, following label directions, then rinse thoroughly

**COVERAGE:** One gallon (3.78L) covers 2,000 square feet (180 square meters).

**CLEAN UP:** N/A

**DISPOSAL:** Use up or give away excess product . Contains surfactants. Do not reuse container. Empty container may be recycled or placed in trash.

**HANDLING & STORAGE:** Avoid extreme temperatures. Store in a cool, dry area. Close container after each use. If frozen, thaw and mix before use.

---

**APPLICATION METHODS:** Apply new finish with mop, sponge or lambs wool pad. When applying more than one coat surface must be completely dry (20 to 40 minutes).

---

- Avoid contact with eyes and skin. dry.
- Use of rubber gloves are recommended to avoid irritation