



PAINTER'S SELECT Everyday Exterior Flat Finish

DESCRIPTION

A durable 100% acrylic latex flat house paint with a 15 year warranty when applied according to all label directions on a properly prepared surface.

JEF-P FORMULA ANALYSIS

Resin Type: Acrylic Latex

Sheen/Type Finish:

1-4 @60° / Flat

Weight per Gallon = 11.47 lbs.

Percent Solids by Weight = 48.0 %

Percent Solids by volume = 33.0 %

Viscosity Range = 95-100

V.O.C. = Less than 50 g/L

Coverage= 350-400 sq. ft. per gallon.

Product Features

- Fade resistant
- Washable
- Easy soap & water clean-up

COLORS AND TINTING

- JEF-9 White
- JEF-P Pastel Base
- JEF-T Tint Base
- JEF-D Deep Base
- JEF-N Neutral Base

RECOMMENDED USE:

Previously painted or primed exterior surfaces including concrete, masonry, vinyl, aluminum and factory primed siding.

THINNING: Thin sparingly with water if necessary for spraying.

DRY TIME: Dries to the touch in 1-2 hours. Recoat if necessary after 4 hours. High humidity or low temperature may increase dry time. After 2-4 weeks, cured paint may be cleaned with a mild, non-abrasive liquid detergent. Dry paint film is mildew resistant.

COVERAGE: 350-400 sq. ft. per gallon depending on the porosity of the surface to be painted.

CLEAN UP & DISPOSAL: Wash tools with warm water and soap immediately after applying. Properly dispose of all soiled rags. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

STORAGE: Protect unused product from freezing.

APPLICATION METHODS

- This paint can be used over latex or oil based paint after properly preparing surface.
- Intermix all containers for color uniformity - may require more than 1 coat.
- Stir thoroughly before and during use. Apply 2 coats.
- Do not apply if rain or dew is expected within 24 hours or if outside temperature could drop below 40°. Use when surface and air temps are between 50-90°.
- Do not apply in hot sun; follow shade around house.
- Do not over spread - Use a premium brush.
- Allow new masonry to cure at least 30 days before coating.

SURFACE PREP

- The surface must be free of dirt, chalk, mildew, and loose peeling paint.
- Damaged wood must be repaired or replaced.
- Cracks, gaps, and holes need to be filled with a paintable acrylic siliconized caulk.
- All bare wood areas need to be properly primed.
- Glossy surfaces need to be sanded and wiped.