



Professional Coatings Good Interior/Exterior Flat Utility – ACP-20

DESCRIPTION

Our good quality interior/exterior latex flat professional coatings.

ACP-20 FORMULA ANALYSIS - 700

RESIN TYPE: Vinyl Acrylic

Sheen/Type Finish:

0-3 @60° / Flat

Weight per Gallon = 11.41 lbs.

Percent Solids by Weight = 46.59 %

Percent Solids by volume = 27.90 %

Viscosity Range = 94-98 KU

V.O.C. = Less than 50 g/L

Product Features

- Good Quality
- Easy soap and water clean-up
- Dries quickly

COLORS AND TINTING

Colors Available:

ACP-20 White (may be tinted with up to 2 oz. of universal colorant per gallon.)

RECOMMENDED USE

Previously painted or properly prepared and primed interior surfaces.

THINNING AND DRY TIME

Thin sparingly with water if necessary for spraying. Dries in 30 minutes. Recoat if necessary after 2 hours. High humidity or low temperature may increase dry time.

COVERAGE:250-400 sq.ft. per gallon depending on the porosity of the surface to be painted.

CLEAN UP: CLEAN UP

Wash tools with warm water and soap immediately after applying.

Properly Dispose of all soiled rags. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only)

STORAGE: Do not expose this product to excessive heat. Close container after each use. Keep from freezing.

APPLICATION METHODS

Average coverage is about 250-400 sq.ft. per gallon depending on the porosity of the surface to be painted.. Do not apply over a surface that has not been thoroughly prepared. Mix thoroughly before using and stir occasionally during application. Intermix all containers for color uniformity. Use a premium brush, roller or pad applicator. May be spray applied. Do not over spread. For best performance; apply two coats on new surfaces after priming.

Surface Prep

- Inadequate surface prep accounts for about 90% of all paint failures
- The surface must be free of dust, dirt, chalk and grime
- Damaged wood must be repaired or replaced.
- Cracks, gaps and holes can be filled with spackle or drywall compound