



Maintenance One Interior Semi-Gloss Flat Latex Flat

DESCRIPTION

A quality interior vinyl acrylic paint that is durable and dries quickly. A one step wall finish that is intended to be used as both a basecoat and a topcoat.

MOC-1 FORMULA ANALYSIS

Resin Type-Vinyl Acrylic

Sheen/Type Finish:

1-4 @60° / Flat

Weight per Gallon = 10.56lbs/gal

Percent Solids by Weight = 37.0 %

Percent Solids by volume = 21.0 %

Viscosity Range = 95-100 KU

V.O.C. = Less than 50 gm/L

Coverage= 250-400 sq. ft. per gallon

Product Features

- High Hiding Formula
- Spatter Resistant
- Easy soap and water clean up.

Colors/Bases

Available:

MOC-1 White

RECOMMENDED USE

New or previously painted or properly prepared and primed interior drywall, including properly cured plaster and texture surfaces.

THINNING: Thin sparingly with water if necessary for spraying.

DRY TIME: Dries to the touch in 30 minutes. Recoat if necessary after 2 hours. High humidity or low temperature may increase dry time. After 2-4 weeks, cured paint may be cleaned with a mild, non-abrasive liquid detergent. Dry paint film is mildew resistant.

COVERAGE: 250-400 sq. ft. per gallon depending on the porosity of the surface to be painted.

CLEAN UP: Wash tools with warm water and soap immediately after applying.

Properly dispose of all soiled rags. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

STORAGE: Protect unused product from freezing.

APPLICATION METHODS

- Do not apply over a surface that has not been thoroughly prepared.
- Stir thoroughly before and during use. Intermix all containers for color uniformity.
- Use a premium nylon/polyester brush, 3/8" nap roller cover or pad applicator.
- Do not over spread.
- For best performance; apply two coats on new surfaces after priming.

SURFACE PREP

- Remove loose paint, wash off dirt and grease with detergent.
- Remove wallpaper.
- Scuff sand and dull glossy surfaces.
- Patch cracks and holes and spot prime.
- For heavily stain areas prime with Start Right Stain Blocking Primer (SRL-1).