



Painter's Select Basic Interior Flat Finish

DESCRIPTION

A good quality interior vinyl acrylic paint.

VF FORMULA ANALYSIS

Resin Type-Vinyl Acrylic

Sheen/Type Finish:

1-4 @60° / Flat

Weight per Gallon = 11.09 lbs/gal

Percent Solids by Weight = 45.0. %

Percent Solids by volume = 27.0 %

Viscosity Range = 100-105 KU

V.O.C. = Less than 50 g/L

Coverage= 250-400 sq. ft. per gallon

Product Features

- High Hiding Formula
- Washable
- Low Odor
- Low VOC
- Mildew Resistant Finish

Colors/Bases

Available:

- VF-11 White
- VF-T Tint Base
- VF-4 Navajo White
- VF-6 Ceiling White
- VF-8 Off White
- VF-20 Bone White

RECOMMENDED USE

Previously painted or properly prepared and primed interior surfaces.

THINNING: Thin sparingly with water if necessary for spraying.

DRY TIME: Dries to the touch in 2-4 hours. Recoat if necessary after 4 hours. High humidity or low temperature may increase dry time. After 2-4 weeks, cured paint may be cleaned with a mild, non-abrasive liquid detergent. Dry paint film is mildew resistant.

COVERAGE: 250-400 sq. ft. per gallon depending on the porosity of the surface to be painted.

CLEAN UP: Wash tools with warm water and soap immediately after applying.

Properly dispose of all soiled rags. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only)

STORAGE: Protect unused product from freezing.

APPLICATION METHODS

- Do not apply over a surface that has not been thoroughly prepared.
- Stir thoroughly before and during use. Intermix all containers for color uniformity.
- Use a premium nylon/polyester brush, 3/8" nap roller cover or pad applicator.
- Do not over spread.
- For best performance; apply two coats on new surfaces after priming.

SURFACE PREP

- Remove loose paint, wash off dirt and grease with detergent.
- Remove wallpaper
- Scuff sand and dull glossy surfaces.
- Patch cracks and holes and spot prime.
- For heavily stain areas prime with Start Right Stain Blocking Primer (SRL-1).
- For drastic color changes or deep, vivid colors prime with Start Right Dark Color Primer (BC-1) tinted to the recommended color.