



## Professional Coatings Best Interior Semi-Gloss Finish – ACP-50 & 51

### DESCRIPTION

Our best quality interior latex semi-gloss professional coatings.

#### ACP-50 FORMULA ANALYSIS

Resin Type: Vinyl Acrylic/Vinyl Acetate-Ethylene

Sheen/Type Finish:

35-45 @60° / Semi-Gloss

Weight per Gallon = 10.59 lbs.

Percent Solids by Weight = 48.06 %

Percent Solids by volume = 36.79 %

Viscosity Range = 90-95 KU

V.O.C. = Less than 50 g/L

#### Product Features

- Best Quality
- Easy soap and water clean-up
- Dries quickly

#### COLORS AND TINTING

ACP-50 White (may be tinted with up to 2 oz. of universal colorant per gallon.)

ACP-51 Off White

#### RECOMMENDED USE

Previously painted or properly prepared and primed interior surfaces.

#### THINNING AND DRY TIME

Thin sparingly with water if necessary for spraying. Dries in 30 minutes. Recoat if necessary after two hours. High humidity or low temperature may increase dry time.

**COVERAGE:** 250-400 sq.ft. per gallon depending on the porosity of the surface to be painted.

#### CLEAN UP: CLEAN UP

Wash tools with warm water and soap immediately after applying.

Properly Dispose of all soiled rags. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only)

**STORAGE:** Do not expose this product to excessive heat. Close container after each use. Keep from freezing.

#### APPLICATION METHODS

Average coverage is about 250-400 sq.ft. per gallon depending on the porosity of the surface to be painted.. Do not apply over a surface that has not been thoroughly prepared. Mix thoroughly before using and stir occasionally during application. Intermix all containers for color uniformity. Use a premium brush, roller or pad applicator. May be spray applied. Do not over spread. For best performance; apply two coats on new surfaces after priming.