



# Start Right Interior Ceiling Paint

## DESCRIPTION

A premium interior acrylic paint that is designed to meet the highest expectations of the most demanding consumer.

**CBW FORMULA ANALYSIS**  
Resin Type-Vinyl Acrylic /Acrylic  
Sheen/Type Finish:  
1-4 @60° / Flat  
Weight per Gallon = 11.48 lbs/gal  
Percent Solids by Weight = 48.0 %  
Percent Solids by volume = 29.0 %  
Viscosity Range = 95-100 KU  
V.O.C. = Less than 50 g/L  
PVC = 68.68 %  
Coverage=250-400 sq. ft. per gallon.

## Product Features

- Hides Ceiling Defects
- Ultra Flat Finish
- Non-Spatter Formula
- Quick Dry
- Soap & Water Clean -up

## Colors/Bases

**Available:**  
CBW- White

## RECOMMENDED USE

Previously painted or properly prepared and primed interior ceilings. Hides minor imperfections.

**THINNING:** Thin sparingly with water if necessary for spraying.

**DRY TIME:** Dries to the touch in 1-2 hours. Recoat if necessary after 4 hours. High humidity or low temperature may increase dry time. After 2-4 weeks, cured paint may be cleaned with a mild, non-abrasive liquid detergent. Dry paint film is mildew resistant.

**COVERAGE:** 250-400 sq. ft. per gallon depending on the porosity of the surface to be painted.

**CLEAN UP:** Wash tools with warm water and soap immediately after applying.

Properly dispose of all soiled rags. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

**STORAGE:** Protect unused product from freezing.

---

## APPLICATION METHODS

- Do not apply over a surface that has not been thoroughly prepared.
- Stir thoroughly before and during use.
- Use a premium nylon/polyester brush, 3/8" nap roller cover or pad applicator.
- Do not over spread.
- For best performance; apply two coats on new surfaces after priming.

---

## SURFACE PREP

- Remove loose paint, wash off dirt and grease with detergent.
- Scuff sand and dull glossy surfaces.
- Patch cracks and holes and spot prime.
- For heavily stain areas prime with Start Right Stain Blocking Primer (SRL-1).