



Professional Coatings Exterior Alkyd Stain Blocking Primer/Undercoat

DESCRIPTION : Our best painters quality Professional Coatings Exterior Stain Blocking Primer/Undercoat with outstanding adhesion to problem surfaces. Use on all exterior wood surfaces.

ACP-64 Resin Type-Highly pigmented long oil alkyd

Sheen/Type Finish:

15-22 @60° / Primer

Weight per Gallon = 12.0 lbs.

Percent Solids by Weight = 79.0 %

Percent Solids by Volume = 61.0 %

Viscosity Range = 75-80 KU

V.O.C. = Less than 300 g/L

Coverage: 400 sq. ft. per gallon

- Excellent stain blocking properties
- Exceptional penetration
- Highly pigmented for improved hide

Colors

ACP-64 White

RECOMMENDED USE: New or bare wood, factory primed siding, and properly primed metal surfaces . Can also be used as a stain blocker to seal tannic acid bleed-through.

THINNING: Use as is.

DRY TIME: Dries thoroughly usually within 24 hours. High humidity or low temperature may increase dry time. Top-coat after 24 hours.

COVERAGE: Average coverage 400 sq. ft. per gallon depending on surface porosity.

CLEAN UP: Use mineral spirits (paint thinner).

DISPOSAL: Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program.

STORAGE: Protect unused product from freezing.

APPLICATION METHODS

- Stir or mix primer before using.
- Apply as is with brush, roller, or paint pad. For spraying information contact your Paint Specialist.
- Do not overspread.
- Avoid painting if outside temperature is below 40°F (4°C) or if rain is expected.

SURFACE PREP

- Remove dirt , mildew, grease, wax and soap residue, loose and peeling paint.
- Dull glossy areas with sandpaper.
- Repair loose or broken siding, brittle caulk, clogged or leaking guttering.
- Putty all nail heads.
- Caulk all seams with a siliconized acrylic caulk.