



Professional Coatings Exterior Latex Primer

DESCRIPTION: This 100% acrylic latex primer can be used on exterior wood, concrete, cement blocks, stucco and asbestos cement shingles to provide an excellent surface in preparation for top coating.

ACP-70 Formula Analysis:

Resin Type-Acrylic Latex

Sheen/Type Finish:

1-4 @60° / Primer

Weight per Gallon = 10.50 lbs.

Percent Solids by Weight = 52.0 %

Percent Solids by Volume = 43.0 %

Viscosity Range = 85-90 KU

V.O.C. = Less than 100g/L

Coverage= 250 sq. ft. on rough surfaces and 400 sq. ft. on smooth surfaces.

Product Features

Product Features

- 100 % Acrylic latex
- Excellent high hiding
- Soap and water clean up
- Excellent sealing properties

Colors

ACP-70 White

RECOMMENDED USE: All exterior wood, concrete, cement blocks stucco and masonry.

THINNING: Use as is.

DRY TIME: Dries in 1 hour. Recoat in 4 hours. May be cleaned gently with non-abrasive cleaner after 3 days. Low temperature or high humidity may increase dry time.

COVERAGE: Average coverage 250 - 400 sq. ft. per gallon.

CLEAN UP: Use warm water and soap.

DISPOSAL: Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program.

STORAGE: Protect unused product from freezing.

APPLICATION METHODS

- Stir or mix primer before using.
- Apply as is with brush, roller, or paint pad.
- For spraying information contact your paint specialist.
- Avoid painting if outside temperature is below 50°F (10°C) or if rain is expected.

SURFACE PREP

- Remove dirt, grease, wax and soap residue.
- Dull glossy areas with sandpaper.
- Repair loose or broken siding, brittle caulk, clogged or leaking guttering.
- Putty all nail heads.
- Caulk all seams with a siliconized acrylic caulk.