



Professional Coatings Interior Latex Primer Sealer

DESCRIPTION: This 100% acrylic latex primer can be used on interior wood, concrete, cement blocks to provide an excellent surface in preparation for top coating.

ACP-53 Resin Type-I Acrylic Latex

Sheen/Type Finish:

1-4 @60° / Primer

Weight per Gallon = 11.10 lbs.

Percent Solids by Weight = 44.0 %

Percent Solids by Volume = 26.0 %

Viscosity Range = 100-105 KU

V.O.C. = Less than 100g/L

Coverage: 350 sq. ft. per gallon

Product Features

- Ideal for walls & ceilings
- Fast dry
- Soap & water clean-up
- High hiding
- Excellent hold-out

Colors

ACP-53 White

RECOMMENDED USE: New or unsealed interior drywall, non-staining wood, plaster, brick, stone and concrete surfaces.

THINNING: Use as is.

DRY TIME: Dries in 1/2 hour. Topcoat after 6 hours. Allow 24 hours before sanding. Low temperature or high humidity may increase dry time.

COVERAGE: Average coverage 350 sq. ft. per gallon depending on porosity of the surface.

CLEAN UP: Use warm water and soap.

DISPOSAL: Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program.

STORAGE: Protect unused product from freezing.

APPLICATION METHODS:

- Stir or mix primer before using.
- Apply as is with brush, roller, or paint pad.
- For spraying information contact your paint specialist.
- Do not overspread.
- Primer may be tinted with up to 4 oz. of colorant per gallon.

SURFACE PREP:

- Remove dirt, grease, wax and soap residue.
- Dull glossy areas with sandpaper.
- Patch cracks and holes.
- Sand smooth when dry then prime.
- New plaster must be properly cured before priming.
- New wood with tannic acid bleed may require an oil base primer/sealer.