



Painter's Select Specialty Exterior Latex Zone Marking Paint

DESCRIPTION

Exterior Latex Zone Marking paint ideal for marking curbs, parking lots, factory floors and warehouses. To be used with automatic marking equipment.

1013/1014 FORMULA ANALYSIS

Resin Type-Acrylic Latex

Sheen/Type Finish:

1-4 @60° / Flat

Weight per Gallon = 13.57 lbs.

Percent Solids by Weight = 76.0%

Percent Solids by volume = 59.0%

Viscosity Range = 85-90 KU

V.O.C. = Less than 50g/L

Product Features

- Dries Quickly
- Durable
- Weather and fade resistant

Colors Available:

1013 White

1014 Yellow

RECOMMENDED USE

For marking curbs and safety zones on streets and parking lots. May also be used for marking playgrounds, tennis courts, safety and storage areas in factories and warehouses.

THINNING: Thin only if necessary; using water and not exceeding 1 pint per gallon.

DRY TIME: Sets up in 10-20 minutes. High humidity or low temperature may increase dry time.

CLEAN UP: Wash tools with warm water and soap immediately after applying.

Properly dispose of all soiled rags. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

STORAGE: Protect unused product from freezing.

COVERAGE:

Width of line

3" (76.2mm)

4" (101.6 mm)

5" (127 mm)

6" (152.4 mm)

Linear feet per gallon

600 feet (187 meters)

450 feet (137 meters)

350 feet (110 meters)

300 feet (91 meters)

Coverage is based on applying the average wet film at 14 mils 125 sq. ft. per gallon.

APPLICATION METHODS

- Stir paint before and during use. Apply with brush, marking roller or line striping equipment.
- No thinning is necessary (see paint specialist for details). Avoid marking if surface temperature is below 40°F (5°C) or rain is expected.

SURFACE PREP

- Clean surface to remove dirt, grease, oil and loose and peeling paint.
- When applied over emulsified coal tar compounds and sealers the surface must first age 7 days.