



## Painter's Select Specialty Exterior Oil Base Enamel Zone Marking

### DESCRIPTION

Exterior Oil Base Zone Marking Paint is ideal for marking curbs, parking lots, factory floors and warehouses. For use with automatic marking equipment.

#### 1010/1012 FORMULA ANALYSIS

Resin Type-Alkyd

Sheen/Type Finish:

1-4 @60° / Flat

Weight per Gallon = 10.87lbs.

Percent Solids by Weight = 66.0 %

Percent Solids by Volume = 49.0 %

Viscosity Range = 75-80

V.O.C. = Less than 450 g/L

#### Product Features

- Weather Resistant
- Fade Resistant

#### Colors Available:

- 1010 White
- 1012 Yellow

#### RECOMMENDED USE

For marking curbs and safety zones on streets and parking lots. May also be used for marking playgrounds, tennis courts, safety and storage areas in factories and warehouses.

**THINNING:** Do NOT thin

**DRY TIME:** Sets to touch in 10-20 minutes. High humidity or low temperature may increase dry time.

**CLEAN UP:** Wash tools with mineral spirits (paint thinner).

Properly dispose of all soiled rags. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

**STORAGE:** Do not expose this container to excessive heat. Close container after each use.

#### COVERAGE:

##### Width of line

3" (76.2mm)

4" (101.6 mm)

5" (127 mm)

6" (152.4 mm)

##### Linear feet per gallon

600 feet (187 meters)

450 feet (137 meters)

350 feet (110 meters)

300 feet (91 meters)

Coverage is based on applying the average wet film at 14 mils 125 sq. ft. per gallon.

#### APPLICATION METHODS

- Stir paint before and during use.
- Apply with brush, marking roller or line striping equipment.
- No thinning is necessary (see paint specialist for details).

#### SURFACE PREP

- Clean surface to remove dirt, grease, oil and loose and peeling paint.
- When applied over emulsified coal tar compounds and sealers the surface must first age 7 days.