



Painter's Select Specialty Exterior Latex Barn & Fence Paint

DESCRIPTION

A durable latex barn & fence paint that dries quickly, great for barns, fences and out buildings.

900 FORMULA ANALYSIS

Resin Type- Vinyl Acrylic

Sheen/Type Finish:

1-4 @60° / Flat

Weight per Gallon = 10.47 lbs.

Percent Solids by Weight = 35.0 %

Percent Solids by volume = 21.0 %

Viscosity Range = 92-96 KU

V.O.C. = Less than 50 g/L

Coverage=350-400 sq. ft. per gallon

Product Features

- Fade resistant coating
- Harmless to livestock
- Soap and water clean-up

Colors Available:

900 White

940 Ranch Red

980 Black

RECOMMENDED USE

All barns, fences, sheds and other exterior ranch and industrial buildings, including concrete, brick and stucco.

THINNING: Do NOT Thin.

DRY TIME: Dries in 1-2 hours. High humidity may increase dry time. Recoat overnight if necessary.

COVERAGE: 350-400 sq. ft. per gallon depending on surface porosity.

CLEAN UP: Clean immediately with soap and water.

Properly dispose of all soiled rags. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

STORAGE: Close container after each use. Keep from freezing.

APPLICATION METHODS

- Stir or mix before and during use.
- Intermix all containers for color uniformity.
- On unpainted or bare surfaces use an exterior oil base primer.
- On concrete, brick and stucco, use 2 coats of this product.
- Use a proper metal primer when painting bare metal.
- Apply paint liberally using a brush, pad or spray.
- For spraying information contact your paint specialist.
- Avoid painting if outside or surface temperature could drop below 50°F (10°C) within 12 hours or if rain is expected.

SURFACE PREP

- Remove dirt, mildew, grease, wax, soap residue and loose and peeling paint.
- Glossy areas must be dulled by sanding.
- Correct all areas in need of repair, such as loose or broken siding, brittle caulk, clogged or leaking gutters.
- Putty all nail heads. Caulk all seams with a siliconized acrylic caulk.