



Premium Décor Interior/Exterior Waterbased Acrylic Enamel

DESCRIPTION

A premium quality interior/exterior acrylic paint. This low odor, environmentally friendly product is extra durable and washable.

COLORS & Bases

- PDL-1 Gloss White
- PDL-2 Gloss Black
- PDL-3 Satin White
- PDL-12 Ivory
- PDL-16 Almond
- PDL-30 Royal Blue
- PDL-33 Country Blue
- PDL-40 Sunflower Yellow
- PDL-50 Hunter Green
- PDL-60 Leather Brown
- PDL-70 Slate Gray
- PDL-71 Pewter Gray
- PDL-96 Fiesta Red
- PDL-97 Hot Red
- Pastel, Tint, Deep, Neutral Base

Product Features

- Fast Drying
- Soap & Water Clean-up
- One Coat Coverage

PDL FORMULA ANALYSIS-WHITE

Resin Type-Acrylic Latex

Sheen/Type Finish:

60 + at 60°/Gloss

Weight per Gallon = 10.03

Percent Solids by Weight = 44.0

Percent Solids by Volume = 32.0

Viscosity = 80-90 KU

V.O.C. = Less than 250g/L.

Coverage=350-400 sq. ft. per gallon.

RECOMMENDED USE: Indoor or outdoor furniture, primed wood or primed metal, wood trim and crafts. Not recommended for use as a house paint.

THINNING: DO NOT THIN.

DRY TIME: Dries in 2 - 4 hours. Repeat if necessary after 8 hours. May be cleaned gently with non-abrasive cleaner after 3 days. Low temperature or high humidity may increase dry time.

CLEAN UP: Wash tools with soap and water immediately after painting. Remove paint spatters promptly with a wet cloth. Properly dispose of all soiled rags. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

STORAGE: Do not expose this container to excessive heat. Close container after each use. Keep from freezing.

APPLICATION: Stir or mix paint before using and intermix all containers for color uniformity. As-is 1 - 2 coats with brush or paint pad. Thin sparingly with water if necessary for spraying. Do not overspread. Average coverage 400 sq. ft. per gallon.

SURFACE PREP:

- Remove dirt, mildew, grease, wax & soap residue.
- Dull glossy areas with sandpaper.
- Sand rough surfaces smooth.
- Prime bare wood with proper oil base primer.
- On metal, use proper metal primer.