



## WX-O Rust Interior/ Exterior Acrylic DTM Enamel

### DESCRIPTION

Interior/Exterior 100% Acrylic Direct to Metal Rust Preventative Enamel dries quickly with low odor. Superior rust protection resists abrasion, weathering and fading.

### WXO FORMULA ANALYSIS

Resin Acrylic Poymer

Sheen/Type Finish:

60 + at 60°/Gloss

Weight per Gallon = 9.90 pounds

Percent Solids by Weight = 38.0 %

Percent Solids by Volume = 14.0 %

Viscosity = 90-95 KU

V.O.C. = Less than 100 g/L

Coverage= 400-450 sq. ft. per gallon.

MPI# 48 Govt. Approved

### Product Features

- For interior & exterior metal substrates only
- Soap & Water Cleanup
- Lower odor

### Colors

WXO -1

**RECOMMENDED USE:** Interior or exterior metal surfaces, such as file cabinets, fencing, metal drains, piping, and tools. **Ideal for metal roofs.**

**THINNING:** DO NOT THIN.

**DRY TIME:** Usually dries in 2 - 4 hours. Low temperature or high humidity may increase dry time.

**CLEAN UP:** Clean up with soap and water. To recycle or properly dispose of paint in your community, call 1-800-CLEANUP (USA only).

**STORAGE:** Do not expose this container to excessive heat. Close container after each use.

---

**APPLICATION:** Stir thoroughly before and during use. Apply as is with a good quality brush, roller or paint pad . Do not overspread. Surface temperature must be above 50°F (10°C). Do not apply in the hot sun. Do not apply if rain or dew is expected. May also be sprayed.

---

### SURFACE PREP:

- Remove all dirt, dust, chalk, grease, oil, loose rust and paint.
- Wipe bare metal with mineral spirits to remove oil and grease.
- Dull glossy surfaces with sandpaper.
- Prime all bare metal with proper X-O Rust Primer for optimum protection of surface.
- Topcoat within 72 hours after priming.