



Exterior 100% Acrylic Wood Toned UV Sealant & Protector - WTSP

DESCRIPTION: 100% Acrylic Water Repellent for natural or pressure treated wood decks & siding.

Product Features

- For wood substrates only
- Ideal for natural or pressure-treated wood decks & siding
- Ultraviolet reflectors retard graying & sun damage
- Toned transparent coating enhances wood grain & color
- Water repellent coating resists scuffing

WTSP Wood Toned

WTSP Formula Analysis:

Resin Type=Acrylic Latex
Weight per Gallon=8.43 lbs/gal
Percent Solids by Weight=8.19%
Percent Solids by Volume=7.21%
Viscosity=65-70 KU
VOC= Less than 100 g/L

RECOMMENDED USE: Exterior above ground natural & pressure-treated woods, including cedar, redwood, fir and pine. Ideal for wood siding, decks and all exterior wood surfaces.

THINNING: DO NOT THIN

DRY TIME: Usually dries within 24 hours. High humidity or low temperatures may increase dry time.

COVERAGE: 150-350 sq. ft. per gallon first coat, 350-450 sq. ft. per gallon second coat depending on the porosity of the wood.

CLEAN UP: Use soap & water before stain dries.

DISPOSAL: ENVIRONMENTAL TIP: Full: Give remaining product to neighbors or community organization. Partially full: (If state or local regulations allow) Pour residue into absorbent material. When dry, dispose of in trash for pick up. Empty: This container may be accepted in a recycling program. To recycle or properly dispose of paint in your community call 1-800-CLEANUP (USA only) or visit www.Earth911.org

STORAGE: Do not expose this container to excessive heat. Close container after each use. Keep from freezing.

APPLICATION:

- Stir and mix wood sealer before and during use.
- Intermix all containers to assure color uniformity. Test stain on wood first for penetration and color.
- Apply as is with brush, roller, pad or spray . Back brush immediately if roller or spray applied.
- DO NOT THIN.**
- Only one coat is recommended.
- Apply sealant / protector 2 or 3 boards at a time going across the entire length, keeping a wet edge.
- Avoid treating wood if temperature is below 50°F (10°C) or rain is expected within 24 hours.
- Average coverage 150-350 sq. ft per gallon (3.78L) depending on the porosity of the wood.
- Do not apply over a surface that has not been thoroughly prepared. Do not apply indoors.