



## Exterior 100% Acrylic Semi-Transparent Deck, Siding & Fence Stain - STL

### DESCRIPTION

100% Acrylic Semi-Transparent Deck, Siding & Fence Stain for natural or pressure treated wood decks, siding & fences. Helps wood stand up to the harshest weather elements

### STL FORMULA ANALYSIS

Resin Type – Acrylic Latex

Sheen/Type Finish:

0-20 @60° / Penetrating Stain

Weight per Gallon = 8.64 lbs.

Percent Solids by Weight = 18.11

Percent Solids by volume = 15.11

Viscosity Range = 60-70 KU

V.O.C. = Less than 100 g/L

### Product Features

- Ideal for natural or pressure-treated wood decks
- Acrylic formula scuff and fade resistant
- Deep penetrating protection repels water
- Enhances wood grain & texture

### COLORS AND TINTING

STL-7 Cedar

STL-10 Redwood

STL-LT Light Base

STL-N Neutral Base

**RECOMMENDED USE:** Exterior above ground natural & pressure-treated woods including cedar, redwood, fir and pine. Also provides excellent protection while maintaining natural appearance to siding, shakes, wood shingles, landscape timbers and decks. MPI approved.

**THINNING:** DO NOT THIN

**DRY TIME: 77°F @50% humidity:** Dry to the touch within 2 to 4 hours. Recoat usually within 24 hours. High humidity or low temperatures may increase dry time. Tinting capability in limited number of colors..

**COVERAGE:** 150-250 sq. ft. per gallon first coat, 350-450 sq. ft. per gallon second coat, depending on the porosity of the wood.

**CLEAN UP & DISPOSAL:** Wash tools with warm water and soap immediately after application. Call 1-800-CLEANUP (USA only) or visit [www.Earth911.org](http://www.Earth911.org). Properly dispose of used rags. Protect unused portion from freezing

**STORAGE:** Do not expose this container to excessive heat. Close container after each use. Keep from freezing.

### APPLICATION:

- Apply only to bare wood surfaces that have been properly prepared and cleaned.
- ONLY ONE COAT IS RECOMMENDED
- Do not apply if rain or dew is expected within 24 hrs or if outside temperature could drop below 50°F
- Do not apply in hot sun.
- Stir thoroughly before and during use.
- Intermix all containers for uniform color.
- Use a premium brush or pad applicator.
- A pump-up sprayer or roller can be used to apply the stain but back brushing with a brush is necessary to get the stain into the wood.
- DO NOT OVER APPLY.
- Spread well, do not puddle or accumulate on wood surface.
- Moving left to right, apply to two or three boards at a time leaving a “wet edge” to prevent lapping.
- Saturate end grain.