# Safety Data Sheet

# 1. Identification

Product Information: WXO-20

Product Name: X-O Rust Waterbase Anti-Rust Brush-On Enamel (Seal Brown)

Recommended Use: Rust Preventative

Application Method: No Information

Supplied by: GPM

201 Jandus Road Cary, IL 60013

Telephone: (847) 639-5383

Emergency Telephone: (866)257-3981

## 2. Hazards Identification

**EMERGENCY OVERVIEW:** This product is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

#### **GHS Classification**

No GHS Classifications were found

#### Symbol(s) of Product

No GHS Symbols Exist

## Signal Word

No Signal Word has been assigned

## Possible Hazards

1% of the mixture consists of ingredients of unknown acute toxicity

# 3. Composition/Information on Ingredients

Chemical Name	CAS-No.	<u>Wt. %</u>	GHS Symbols	<b>GHS Statements</b>
POLYURETHANE RESIN	Proprietary	1.0-2.5	No Information	No Information
CARBON BLACK	1333-86-4	0.1-1.0	No Information	No Information
SODIUM NITRITE	7632-00-0	0.1-1.0	GHS03-GHS06	H272-301
LITHIUM HYDROXIDE MONOHYDRATE	1310-66-3	< 0.1	No Information	No Information

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

## 4. First-aid Measures



FIRST AID - INHALATION: Remove person to fresh air. If signs/symptoms continue, get medical attention.

FIRST AID - SKIN CONTACT: WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND CLEAN BEFORE REUSE.

FIRST AID - EYE CONTACT: FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL HELP IF IRRITATION PERSISTS.

FIRST AID - INGESTION: Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested. Have the victim drink 8 to

10 ounces (240 - 300 ml) of water to dilute the material in the stomach. If vomiting occurs naturally, have the victim lean forward to reduce the risk of aspiration. Consult a physician immediately.

# 5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Container may rupture on heating.

**SPECIAL FIREFIGHTING PROCEDURES:** Use a self-contained breathing apparatus with full facepiece operated in pressure-demand or other positive pressure mode. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog

## 6. Accidental Release Measures

**ENVIRONMENTAL PRECAUTIONS: No Information** 

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: ISOLATE HAZARD AREA AND KEEP UNNECESSARY PEOPLE AWAY. DO NOT ALLOW THE LIQUID TO ENTER INTO ANY SEWERS, ONTO THE GROUND OR INTO ANY BODY OF WATER. FOR LARGE SPILLS, USE A DIKE AND PUMP INTO APPROPRIATE CONTAINERS. SMALL SPILLS, DILUTE WITH WATER AND RECOVER OR USE NON-COMBUSTIBLE ABSORBENT MATERIAL AND SHOVEL INTO WASTE CONTAINERS.

# 7. Handling and Storage





HANDLING: KEEP FROM FREEZING

STORAGE: Store in a cool dry area. KEEP OUT OF REACH OF CHILDREN.

## 8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	OSHA PEL-TWA	OSHA PEL-CEILING
POLYURETHANE RESIN	N.E.	N.E.	N.E.	N.E.
CARBON BLACK	3 mg/m3	7 mg/m3	3.5 mg/m3	N.E.
SODIUM NITRITE	N.E.	N.E.	N.E.	N.E.
LITHIUM HYDROXIDE MONOHYDRATE	N.E.	N.E.	N.E.	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

## **Personal Protection**



**RESPIRATORY PROTECTION:** In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator.



SKIN PROTECTION: Sensitive individuals should wear gloves to prevent repeated contact.



EYE PROTECTION: Safety glasses with side-shields



**OTHER PROTECTIVE EQUIPMENT:** No Information



#### **HYGIENIC PRACTICES:** Wash hands before eating, drinking, or smoking.

# 9. Physical and Chemical Properties

Appearance: Thick Brown Liquid Physical State: Liquid

Odor: **Odor Threshold:** Slight Ammonia Odor No Information Density, g/cm3: 0.000 :Ha No Information Freeze Point. °C: Viscosity: No Information No Information Solubility in Water: Partition Coefficient, n-octanol/ No Information No Information

Decomposition temperature, °C No Information water:

Boiling Range, °C: 98 - 104 Explosive Limits, %: N/A

Combustibility:Does not Support Combustion<br/>Evaporation Rate:Flash Point, °C:Not ApplicableVapor Density:No InformationAuto-Ignition Temperature, °CNo InformationVapor Pressure, mmHg:No Information

(See "Other information" Section for abbreviation legend)

# 10. Stability and Reactivity

STABILITY: THIS MATERIAL IS STABLE UNDER NORMAL STORAGE AND HANDLING CONDITIONS.

CONDITIONS TO AVOID: AVOID HIGH TEMPERATURES AND FREEZING.

**INCOMPATIBILITY:** No Information

HAZARDOUS DECOMPOSITION PRODUCTS: MAY GENERATE TOXIC OR IRRRITATING COMBUSTION PRODUCTS. MAY GENERATE CARBON MONOXIDE GAS.

# 11. Toxicological Information



## **Practical Experiences**

**EFFECT OF OVEREXPOSURE - INHALATION:** Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes).

EFFECT OF OVEREXPOSURE - SKIN CONTACT: PROLONGED OR REPEATED CONTACT MAY CAUSE IRRITATION.

EFFECT OF OVEREXPOSURE - EYE CONTACT: MILD EYE IRRITANT.

EFFECT OF OVEREXPOSURE - INGESTION: May be harmful if swallowed. May cause gastrointestinal disturbance.

**EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS:** Under normal use conditions, this product is not expected to cause adverse health effects.

CARCINOGENICITY: IARC lists Carbon Black as a possible human carcinogen (Group 2B)

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Contact

# **Acute Toxicity Values**

The acute effects of this product have not been tested. Data on individual components are tabulated below

CAS-No.	<u>Chemical Name</u>	Oral LD50	Dermal LD50	Vapor LC50
Proprietary	POLYURETHANE RESIN	>2000 mg/kg	N.I.	N.I.
1333-86-4	CARBON BLACK	>8000 mg/kg	>3000 mg/kg	N.I.
7632-00-0	SODIUM NITRITE	180 mg/kg	N.I.	N.I.

N.I. = No Information

# 12. Ecological Information

**ECOLOGICAL INFORMATION:** No Information

# 13. Disposal Information



## **Product**

**DISPOSAL METHOD:** DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. ALL DISPOSAL METHODS MUST BE IN COMPLIANCE WITH ALL FEDERAL, STATE/PROVINCIAL, AND LOCAL LAWS AND REGULATIONS.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: ISOLATE HAZARD AREA AND KEEP UNNECESSARY PEOPLE AWAY. DO NOT ALLOW THE LIQUID TO ENTER INTO ANY SEWERS, ONTO THE GROUND OR INTO ANY BODY OF WATER. FOR LARGE SPILLS, USE A DIKE AND PUMP INTO APPROPRIATE CONTAINERS. SMALL SPILLS, DILUTE WITH WATER AND RECOVER OR USE NON-COMBUSTIBLE ABSORBENT MATERIAL AND SHOVEL INTO WASTE CONTAINERS.

# 14. Transport Information

#### SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT Proper Shipping Name:No InformationPacking Group:No InformationDOT Technical Name:No InformationHazard SubClass:No InformationDOT Hazard Class:No InformationResp. Guide Page:No Information

**DOT UN/NA Number:**No Information

# 15. Regulatory Information

# U.S. Federal Regulations:

## **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Health Hazard, Chronic Health Hazard

## **SARA SECTION 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical NameCAS-No.AMMONIUM HYDROXIDE1336-21-6MAGNESIUM NITRATE10377-60-3

## TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

## U.S. State Regulations:

## **NEW JERSEY RIGHT-TO-KNOW:**

The following materials are non-hazardous, but are among the top five components in this product.

Chemical NameCAS-No.WATER7732-18-5ACRYLIC POLYMERProprietaryC.I. Pigment Yellow 4251274-00-1Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-<br/>pentanediol25265-77-4

#### PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical NameCAS-No.WATER7732-18-5ACRYLIC POLYMERProprietaryC.I. Pigment Yellow 4251274-00-1Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-<br/>pentanediol25265-77-4

#### **CALIFORNIA PROPOSITION 65 CARCINOGENS**

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

 Chemical Name
 CAS-No.

 CARBON BLACK
 1333-86-4

 ETHYLBENZENE
 100-41-4

 1,4-DIOXANE
 123-91-1

## **CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

International Regulations: As follows -

#### **CANADIAN WHMIS:**

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class No Information

## 16. Other Information

Revision Date: 8/5/2016 Supersedes Date: New MSDS

Reason for revision: No Information

Datasheet produced by: Regulatory Department

**HMIS Ratings:** 

 Health:
 1
 Flammability:
 0
 Reactivity:
 0
 Personal Protection:
 N.I.

## Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H272 May intensify fire; oxidiser. H301 Toxic if swallowed.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS03

**GHS06** 



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.